



SpekTrix

Designed for optimal ease-of-use, the Adamson SpekTrix is a three-way active loudspeaker that employs two dedicated 8" Kevlar Neodymium drivers and one 1.4" exit high frequency compression driver mounted on a proprietary wave shaping sound chamber. SpekTrix offers a defined coverage pattern of 120° x 5° (H x V).

The AIR™ rigging system is simple and effective, consisting of a laser-cut revolving disk allowing for 6 splay positions. The enclosure is also available with EIR™ installation rigging (-i), a plate system that reduces cost and weight.

Specifications

Frequency Range (+/-3 dB)	100 Hz - 18 kHz
Nominal Directivity (-6 dB) H x V	120° x 5°
Maximum Peak SPL **	139.1 dB
Components LF	ND8-L 8" Kevlar Neodymium Driver
Components MF	ND8-M 8" Kevlar Neodymium Driver
Components HF	B&C DE900 3" Diaphragm / 1.4" Exit Compression Driver
Nominal Impedance LF	8 Ω
Nominal Impedance MF	8 Ω
Nominal Impedance HF	8 Ω
Power Handling (AES / Peak) LF	250 / 1000 W
Power Handling (AES / Peak) MF	250 / 1000 W
Power Handling (AES / Peak) HF	110 / 440 W
Rigging	AIR™ Revolving Disc System (Touring) or EIR™ Plate System (Install)
Connection	2x Speakon™ NL8
Height Front (mm / in)	220 / 8.6
Width (mm / in)	710 / 27.9
Depth (mm / in)	480 / 18.9
Weight (kg / lbs)	29 / 62
Processing	Lake, Powersoft, XTA

**12 dB crest factor pink noise at 1m, free field, using specified processing and amplification

